

AIRLED KÜÇÜK KÜP

Product Specifications/Ürün Özellikleri

Product Name	: Airlid- Küçük Küp
Dimension	: H23 /W27 mm
PCB Increment	: Power Connection and cut point every 50 mm
LED pitch	: 8-10 mm
Chip	: Samsung
Beam Angle	: 180°
Colours	: White
Bin/Step	: 3 step Macadam ellipse
CRI	: 85
Lifetime	: 50.000 hours
Operating Temp.	: -40° . +200
IP Rating	: IP68
Mounting	: Nötr Silicon
Minumum bend radius	: 100 mm
Connection	: Hardwire tails or male/famale connectors
Control	: 0-10/DMX/DALI
Case Type	: Flexible Silicon Case



Performance Data/ Performans Verileri (for 1000mm)

Power consumption	: 13 W
Supply voltage	: 24 V DC
Supply current	: 0.5 A
Lumious flux	: 1445 Lm


Color Characteristics / Renk Özellikleri

Correlated Color Temperatur (CCT)	: 3000 K
Colour rendering index (CRI,RA)	: 85
Chromatic Coordinates	: 0.4 A

Light Output/ Işık Çıkışı

Total Light cutput (Lumens)	: 1445
Luminaire efficacy (lm/W)	: 85.13
Beam angle	: 180°

Tecnical Drawing/ Teknik Çizim



Product and Power Options

Product Name/Number of LEDs	Max Lenght (m)	Light Color	Voltage[V]	Power [W/mt]	Luminous Flux [lm/m]	Weight (mt/gr)
KÜÇÜK KÜP/126LED	20 m	WW	24C DC	12	1445	6Ü0
KÜÇÜK KÜP/126LED	20 m	NW	24C DC	12	1532	6Ü0
KÜÇÜK KÜP/126LED	20 m	CW	24C DC	12	1503	6Ü0
KÜÇÜK KÜP/126LED	20 m	WW	12V DC	7,2	723	6Ü0
KÜÇÜK KÜP/126LED	20 m	NW	12V DC	7,2	766	6Ü0
KÜÇÜK KÜP/126LED	20 m	CW	12V DC	7,2	751	6Ü0
KÜÇÜK KÜP/126LED	20 m	RGB-PIXEL	24V DC	14,4	-	6Ü0
KÜÇÜK KÜP/126LED	20 m	RGBW	24V DC	19,2	-	6Ü0
KÜÇÜK KÜP/126LED	20 m	RGB	24V DC	19,2	-	6Ü0



WW; Warm White 3000K
NW; Natural White 4000K
CW; Cold White 6500K

